

## **Datasheet** Security Never Shuts Down

# **Outdoor Full-Color**

**Bullet Network Camera** 

MODEL: VIGI C340













## **■** Smart Detection

Receive notifications and check feeds when someone crosses a boundary, enters an area you've set, or obstructs the camera.



### **Motion Detection**

Get instant notifications when your camera detects motion.




### **Human Detection**

Smarter security alerts focus on human movement instead of flying insects, small animals and leaves.



## **Line-Crossing**

Set a boundary and receive an alert anytime a person crosses it from either or both directions.



#### **Area Intrusion**

Set customized activity zones around key areas for more focused monitoring.



## **Camera Tampering**

Receive alerts when someone obstructs the camera.





#### **Smart IR**

Keeps objects from being under-rendered when far away or overexposed when close to camera at night.



## Wide Dynamic Range

Adjusts for lighting contrast to minimize shadowing effects and renders images true to life.




#### 3D DNR

Removes abnormal pixelation to provide clearer video and eliminate distortion.

## **//** VIGI Surveillance Solution


The VIGI professional surveillance system by TP-Link is dedicated to protecting the business that you've worked hard to build—whenever, wherever.

Outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.



# **I** Flexible Installation

Find the perfect vantage point by simply securing your camera to the ceiling, wall, or pole\*.



# Specifications

Camera	
Image Sensor	1/3" Progressive Scan CMOS
Min. Illumination	0 lux with IR/white Light
Day & Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	DWDR
Lens	
Lens Type	Fixed focal lens, 2.8mm, 4mm, and 6 mm
Aperture	6 mm: F1.6
	4 mm: F1.6
	2.8 mm: F1.6
	2.8mm
	Horizontal FOV: 102°, Vertical FOV: 55°, Diagonal FOV: 122°
Focal Length & FOV	4mm
r o oar zorigan ar o r	Horizontal FOV: 79°, Vertical FOV: 43°, Diagonal FOV: 93°
	6mm Horizontal FOV: 50°, vertical FOV: 27°, Diagonal FOV: 59°
Lens Mount	M12
	IVITZ
Illuminator	
IR LED	Range: 30m;
White LED	Wavelength: 850nm
White LED	Range: 30m
Compression Standard	
Video Compression	Main stream: H.265/H.264
·	Sub-Stream: H.265/H.264
H.264 Type	Main Profile/High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	Main Stream: 256 Kbps to 4 Mbps
	Sub-Stream: 64 Kbps to 512 Kbps

Smart Feature-set		
Smart Event	Area Intrusion Detection, Line-Crossing Detection, Human Detection	
Basic Event	Motion Detection, Video Tampering Detection, Exception (Illegal login)	
Linkage Method	Trigger Notification: ONVIF, HTTPS	
Region of Interest	1 Region	
Image		
Max. Resolution	4MP	
Main Stream	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 2560x1440, 2304x1296, 2048x1280,	
	1920x1080	
Sub-Stream	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps	
	Resolution: 640x480, 352x288, 320x240	
Image Enhancement	BLC/3D DNR/Prevent Overexposure to Infrared Light	
Image Settings	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance Adjustable by Client Software	
Day/Night Switch	Day/Night/Auto/Schedule	
Network		
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS	
General Function	Two Streams, Mirror, Privacy Masks, Password Reset via E-mail, HTTP Listening	
API	ONVIF	
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication	
Simultaneous Live View	3 Main Streams & 3 Sub-Streams	
User/Host	Up to 21 Users	
Client	VIGI Security Manager, VIGI app	
Interface		

Communication Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port
Video Output	No
Reset Button	Yes
SD Card Slot	Yes
Built-in Speaker	Yes
Built-in Microphone	Yes
General	
Operating Temperature	-30–60 °C
Power Supply	12V DC ± 5%, 5.5mm Coaxial Power Plug PoE (802.3af/at, class 0)
Power Consumption	12V DC: Max 5.5W PoE: Class 0
Material	Plastic
Product Dimensions	78*70*174mm
Product Weight	195g
Certifications	CE, RCM, BSMI, VCCI, RoHS, NTRA, KC

Specifications are subject to change without notice and can be found at www.tp-link.com. ©2022 TP-Link