

Ethernet Switches

NSW2010-10T-POE-IN



Features

- Multiple working modes to address your business needs: Default(Normal mode), VLAN(Secure mode), EXTEND(Surveillance mode)
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization
- All metal housing, safe and reliable

Specifications

| | |
|------------------------|--|
| Model | NSW2010-10T-PoE-IN |
| Hardware Specification | |
| Ports Type | 10×100Mbps network ports (RJ45), including 8 PoE ports |
| Forwarding performance | 1.49Mpps |
| Standards | IEEE802.3, IEEE802.3u, IEEE802.3az, IEEE802.3x, IEEE802.3af, IEEE802.3at |

| | |
|----------------------------------|--|
| Switching capacity | 2 Gbps |
| Packet Buffer | 1.625 M bit |
| MAC | 4K |
| Power supply | AC: 100-240 V, 50/60 Hz |
| Max. PoE Power | Max capacity: 120 W, Max capacity for single port: 30 W |
| Cooling Fans | 0 |
| Mean Time Between Failure (MTBF) | > 50000 hours |
| Weight | <1.22 kg |
| Operating humidity | 10%~90% (non-condensing) |
| Storage humidity | 5%~90% (non-condensing) |
| Operating temperature | 0 °C to 40 °C (32 °F to 104 °F) |
| Storage Temperature | -40 °C to 70 °C |
| Dimensions (W×D×H) | 220mm x 150mm x 44mm(8.7"×5.9"×1.7") |
| Working Mode | Default (Normal mode) : All ports can communicate with each other, EXTEND (Surveillance mode): Transmission distance up to 250 meters |
| Indicator | POWER Steady on: AC input is normal, POWER Off: No AC input, PoE Off: No PoE power supply, PoE Steady on: PoE power supply is normal, LINK/ACT Off: No link, LINK/ACT Steady on: Linked, LINK/ACT Flashing: Transmitting data, Speed Off: Linked at 10/100 Mbps, Speed On: Linked at 1000 Mbps |

Ordering Info

| Product Model | Description |
|--------------------|----------------------|
| NSW2010-10T-PoE-IN | Ethernet Switch(PoE) |

Zhejiang Uniview Technologies Co., Ltd.

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document. Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.